

# **Product datasheet**P RF CLAS A DIM 4.5 W/827 E27

## PARATHOM Retrofit CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



 Perfect for decorative installations Domestic applications General illumination Outdoor use in outdoor luminaires only (minimum IP65)

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Very low energy consumption Robust
  against vibrations No UV and near-IR radiation in the light beam Instant 100 % light, no warm-up time Can be easily fitted
  instead of ordinary light bulbs Lower thermal output (compared with the standard reference product)
- Product features Professional LED lamps for line voltage Dimmable Base: E27, B22d Mercury-free lamps Lifetime: up to 15,000 hProduct benefits Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Very low energy consumption Robust against vibrations No UV and near-IR radiation in the light beam Instant 100 % light, no warm-up time Can be easily fitted instead of ordinary light bulbs Lower thermal output (compared with the standard reference product)Areas of application Perfect for decorative installations Domestic applications General illumination Outdoor use in outdoor luminaires only (minimum IP65)



## Product datasheet

#### Technical data

#### **Electrical data**

Rated wattage	4.50 W	
Nominal wattage	4.50 W	
Nominal voltage	220240 V	
Operating frequency	5060 Hz	
Max. lamp no. on circuit break. 10 A (B)	460	
Max. lamp no. on circuit break. 16 A (B)	736	
Claimed equiv. conventional lamp power	40 W	


#### Photometrical data

Nominal luminous flux	470 lm	
Rated luminous flux	470 lm	
Rated color temperature	2700 K	
Color rendering index Ra	≥80	
Light color (designation)	Warm White	
Standard deviation of color matching	≤6 sdcm	
Lumen main.fact.at end of nom.life time	0.70	

## Light technical data

Starting time	< 0.5 s

# Dimensions & weight



Overall length	105.0 mm
Diameter	60.0 mm
Outer bulb	A60
Length	105.0 mm

## Product datasheet

## Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

## Additional product data

Base (standard designation)	E27		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Frosted		
Appropriate disposal acc. to WEEE	Yes		
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)		

## Capabilities

Dimmable	Yes
----------	-----

#### **Certificates & standards**

Energy efficiency class	A++	
Energy consumption	5 kWh/1000h	

## **Country specific categorizations**

Order reference	LEDPCLA40D 4,5W	

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075287327	P RF CLAS A DIM 4.5 W/827 E27	Shipping carton box 10 Pieces Folding carton box	325 mm x 136 mm x 126 mm	5.57 dm <sup>3</sup>	533.00 g

#### Product datasheet

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany